

# Hierarchies of $\omega$ -languages

Jérémie Cabessa

University Joseph Fourier – Grenoble 1

13 February 2009

# Outline

## 1 Introduction

## 2 $\omega$ -languages

## 3 The Cantor space

## 4 The Borel hierarchy

## 5 The Wadge hierarchy

## 6 Conclusion

# Outline

## 1 Introduction

## 2 $\omega$ -languages

## 3 The Cantor space

## 4 The Borel hierarchy

## 5 The Wadge hierarchy

## 6 Conclusion

# Outline

## 1 Introduction

## 2 $\omega$ -languages

## 3 The Cantor space

## 4 The Borel hierarchy

## 5 The Wadge hierarchy

## 6 Conclusion

# Outline

## 1 Introduction

## 2 $\omega$ -languages

## 3 The Cantor space

## 4 The Borel hierarchy

## 5 The Wadge hierarchy

## 6 Conclusion

# Outline


- 1 Introduction
- 2  $\omega$ -languages
- 3 The Cantor space
- 4 The Borel hierarchy
- 5 The Wadge hierarchy
- 6 Conclusion

# Outline

- 1 Introduction
- 2  $\omega$ -languages
- 3 The Cantor space
- 4 The Borel hierarchy
- 5 The Wadge hierarchy
- 6 Conclusion



Descriptive Set Theory provides a general framework for classification problems.





# $\omega$ -languages

- A *language* is a set of words.
- An  $\omega$ -language is a set of infinite words.

## Definition

- An *alphabet* is simply a set whose elements are called *letters*.
- A *word* is a sequence of letters of given alphabet. An *infinite word* is an infinite sequence of letters.
- A *language* is a set of words.
- An  $\omega$ -language is a set of infinite words.

# $\omega$ -languages

- A *language* is a set of words.
- An  $\omega$ -language is a set of infinite words.

## Definition

- An *alphabet* is simply a set whose elements are called *letters*.
- A *word* is a sequence of letters of given alphabet. An *infinite word* is an infinite sequence of letters.
- A *language* is a set of words.
- An  $\omega$ -*language* is a set of infinite words.

# $\omega$ -languages

- A *language* is a set of words.
- An  $\omega$ -language is a set of infinite words.

## Definition

- An *alphabet* is simply a set whose elements are called *letters*.
- A *word* is a sequence of letters of given alphabet. An *infinite word* is an infinite sequence of letters.
- A *language* is a set of words.
- An  $\omega$ -language is a set of infinite words.

# $\omega$ -languages

- A *language* is a set of words.
- An  $\omega$ -language is a set of infinite words.

## Definition

- An *alphabet* is simply a set whose elements are called *letters*.
- A *word* is a sequence of letters of given alphabet. An *infinite word* is an infinite sequence of letters.
- A *language* is a set of words.
- An  $\omega$ -*language* is a set of infinite words.

# $\omega$ -languages

- A *language* is a set of words.
- An  $\omega$ -language is a set of infinite words.

## Definition

- An *alphabet* is simply a set whose elements are called *letters*.
- A *word* is a sequence of letters of given alphabet. An *infinite word* is an infinite sequence of letters.
- A *language* is a set of words.
- An  $\omega$ -language is a set of infinite words.

# $\omega$ -languages

- A *language* is a set of words.
- An  $\omega$ -language is a set of infinite words.

## Definition

- An *alphabet* is simply a set whose elements are called *letters*.
- A *word* is a sequence of letters of given alphabet. An *infinite word* is an infinite sequence of letters.
- A *language* is a set of words.
- An  $\omega$ -*language* is a set of infinite words.

# $\omega$ -languages

- A *language* is a set of words.
- An  $\omega$ -language is a set of infinite words.

## Definition

- An *alphabet* is simply a set whose elements are called *letters*.
- A *word* is a sequence of letters of given alphabet. An *infinite word* is an infinite sequence of letters.
- A *language* is a set of words.
- An  $\omega$ -language is a set of infinite words.

## Example

- We will usually consider the alphabet  $A = \{0, 1\}$ .
- Words on  $A$ :  $w_0 = 01101$ ,  $w_1 = 11101$ , ...
- Infinite words on  $A$ :  $\alpha = 0000 \dots$ ,  $\beta = 1001010 \dots$ , ...
- Language on  $A$ :  $L = \{00, 011, 10, 1101\}$ .
- $\omega$ -Language on  $A$ :  $L = \{0000 \dots, 100 \dots, 1100 \dots\}$ .



## Example

- We will usually consider the alphabet  $A = \{0, 1\}$ .
- Words on  $A$ :  $w_0 = 01101$ ,  $w_1 = 11101$ , ...
- Infinite words on  $A$ :  $\alpha = 0000 \dots$ ,  $\beta = 1001010 \dots$ , ...
- Language on  $A$ :  $L = \{00, 011, 10, 1101\}$ .
- $\omega$ -Language on  $A$ :  $L = \{0000 \dots, 100 \dots, 1100 \dots\}$ .

## Example

- We will usually consider the alphabet  $A = \{0, 1\}$ .
- Words on  $A$ :  $w_0 = 01101$ ,  $w_1 = 11101$ , ...
- Infinite words on  $A$ :  $\alpha = 0000 \dots$ ,  $\beta = 1001010 \dots$ , ...
- Language on  $A$ :  $L = \{00, 011, 10, 1101\}$ .
- $\omega$ -Language on  $A$ :  $L = \{0000 \dots, 100 \dots, 1100 \dots\}$ .

## Example

- We will usually consider the alphabet  $A = \{0, 1\}$ .
- Words on  $A$ :  $w_0 = 01101$ ,  $w_1 = 11101$ , ...
- Infinite words on  $A$ :  $\alpha = 0000 \dots$ ,  $\beta = 1001010 \dots$ , ...
- Language on  $A$ :  $L = \{00, 011, 10, 1101\}$ .
- $\omega$ -Language on  $A$ :  $L = \{0000 \dots, 100 \dots, 1100 \dots\}$ .

## Example

- We will usually consider the alphabet  $A = \{0, 1\}$ .
- Words on  $A$ :  $w_0 = 01101$ ,  $w_1 = 11101$ , ...
- Infinite words on  $A$ :  $\alpha = 0000 \dots$ ,  $\beta = 1001010 \dots$ , ...
- Language on  $A$ :  $L = \{00, 011, 10, 1101\}$ .
- $\omega$ -Language on  $A$ :  $L = \{0000 \dots, 100 \dots, 1100 \dots\}$ .

An abstract machine  $\mathcal{M}$  can be identified with the languages  $L(\mathcal{A})$  that it recognizes.

## Example

The following Muller automaton  $\mathcal{A}$  can be identified with the  $\omega$ -language  $L(\mathcal{A})$  of infinite words with infinitely many 1's.




Hence abstract machines can be considered as specific  $\omega$ -languages!

An abstract machine  $\mathcal{M}$  can be identified with the languages  $L(\mathcal{A})$  that it recognizes.

## Example

The following Muller automaton  $\mathcal{A}$  can be identified with the  $\omega$ -language  $L(\mathcal{A})$  of infinite words with infinitely many 1's.




Hence abstract machines can be considered as specific  $\omega$ -languages!

An abstract machine  $\mathcal{M}$  can be identified with the languages  $L(\mathcal{A})$  that it recognizes.

## Example

The following Muller automaton  $\mathcal{A}$  can be identified with the  $\omega$ -language  $L(\mathcal{A})$  of infinite words with infinitely many 1's.



Hence abstract machines can be considered as specific  $\omega$ -languages!

A decision problem  $P$  can be identified the languages  $L_P$  of all its solutions.

## Example

For instance, consider the following decision problem and language:

- $P$ : Given a finite graph  $G$ , is  $G$  acyclic or not?
- $L_P$ : the set of all acyclic finite graphs (language of solutions).

Then the question “is  $G$  is acyclic?” is **equivalent** to the question “does  $G \in L_P$ ?”.

Hence decision problems can be considered as specific languages!



A decision problem  $P$  can be identified the languages  $L_P$  of all its solutions.

## Example

For instance, consider the following decision problem and language:

- $P$ : Given a finite graph  $G$ , is  $G$  acyclic or not?
- $L_P$ : the set of all acyclic finite graphs (language of solutions).

Then the question “is  $G$  is acyclic?” **is equivalent** to the question “does  $G \in L_P$ ?”.

Hence decision problems can be considered as specific languages!

A decision problem  $P$  can be identified the languages  $L_P$  of all its solutions.

## Example

For instance, consider the following decision problem and language:

- $P$ : Given a finite graph  $G$ , is  $G$  acyclic or not?
- $L_P$ : the set of all acyclic finite graphs (language of solutions).


Then the question “is  $G$  is acyclic?” **is equivalent** to the question “does  $G \in L_P$ ?”.

Hence decision problems can be considered as specific languages!

Therefore a classification of languages induces in particular:

- A classification of abstract machines;
- A classification of decision problems;

Hierarchy of  
languages






Therefore a classification of languages induces in particular:

- A classification of abstract machines;
- A classification of decision problems;

Hierarchy of languages

Sub-hierarchy of abstract machines




Therefore a classification of languages induces in particular:

- A classification of abstract machines;
- A classification of decision problems;


Hierarchy of languages

Sub-hierarchy of abstract machines



Therefore a classification of languages induces in particular:

- A classification of abstract machines;
- A classification of decision problems;



In fact, a given classification of languages induces a classification of “anything that can be coded by a language”!

Therefore descriptive set theory provides a general approach of classification problems.



# The Cantor space

The *Cantor space* is the space of all infinite words of bits.

## Definition

Consider the alphabet  $A = \{0, 1\}$ . The *Cantor space*  $\mathcal{C}$  is the set of all infinite words on  $A$ .

$$\begin{aligned}\mathcal{C} = \{ & 000000 \dots, \\ & 100000 \dots, \\ & 110000 \dots, \\ & 110000 \dots, \\ & \vdots \\ & \dots \}\end{aligned}$$

# The Cantor space

The *Cantor space* is the space of all infinite words of bits.

## Definition

Consider the alphabet  $A = \{0, 1\}$ . The *Cantor space*  $\mathcal{C}$  is the set of all infinite words on  $A$ .

$$\mathcal{C} = \{000000 \dots, \\ 100000 \dots, \\ 110000 \dots, \\ 110000 \dots, \\ \vdots \\ \dots\}$$

## Lemma

*The Cantor space  $\mathcal{C}$  is uncountable. More precisely,  $\text{card}(\mathcal{C}) = \text{card}(\mathbb{R})$ .*


## Proof.

A diagonal argument.



Elements of the Cantor space  $\mathcal{C}$  are infinite words of bits.  
 Elements of the Cantor space  $\mathcal{C}$  “are” the infinite branches of the infinite binary tree.

The Cantor space



Subsets of the Cantor space  $\mathcal{C}$  “are” set of infinite branches of the infinite binary tree.





## Summary:

- Elements of  $\mathcal{C}$  are infinite words of bits.
- Subsets of  $\mathcal{C}$  are  $\omega$ -languages over bits.

## Summary:

- Elements of  $\mathcal{C}$  are infinite words of bits.
- Subsets of  $\mathcal{C}$  are  $\omega$ -languages over bits.



## Summary:

- Elements of  $\mathcal{C}$  are infinite words of bits.
- Subsets of  $\mathcal{C}$  are  $\omega$ -languages over bits.

# The Borel hierarchy

The *Borel hierarchy* is the most common classification of subsets of a given topological space. In our case, we first equip the Cantor space  $\mathcal{C}$  with the following topology:

- The *basic open sets* are the prefix  $\omega$ -languages i.e.

*$B$  is a basic open set*

iff

*$B$  contains all infinite words  
that begin with a given prefix  $p$ .*

- The *open sets* are the arbitrary unions of basic open sets.
- The *closed sets* are the complements of open sets.

# The Borel hierarchy

The *Borel hierarchy* is the most common classification of subsets of a given topological space. In our case, we first equip the Cantor space  $\mathcal{C}$  with the following topology:

- The *basic open sets* are the prefix  $\omega$ -languages i.e.

*B is a basic open set*  
iff  
*B contains all infinite words*  
*that begin with a given prefix p.*

- The *open sets* are the arbitrary unions of basic open sets.
- The *closed sets* are the complements of open sets.

# The Borel hierarchy

The *Borel hierarchy* is the most common classification of subsets of a given topological space. In our case, we first equip the Cantor space  $\mathcal{C}$  with the following topology:

- The *basic open sets* are the prefix  $\omega$ -languages i.e.

*$B$  is a basic open set*

iff

*$B$  contains all infinite words  
that begin with a given prefix  $p$ .*

- The *open sets* are the arbitrary unions of basic open sets.
- The *closed sets* are the complements of open sets.

# The Borel hierarchy

The *Borel hierarchy* is the most common classification of subsets of a given topological space. In our case, we first equip the Cantor space  $\mathcal{C}$  with the following topology:

- The *basic open sets* are the prefix  $\omega$ -languages i.e.

$B$  is a *basic open set*

iff

$B$  contains all infinite words  
that begin with a given prefix  $p$ .

- The *open sets* are the arbitrary unions of basic open sets.
- The *closed sets* are the complements of open sets.

# The Borel hierarchy

The *Borel hierarchy* is the most common classification of subsets of a given topological space. In our case, we first equip the Cantor space  $\mathcal{C}$  with the following topology:

- The *basic open sets* are the prefix  $\omega$ -languages i.e.

$B$  is a *basic open set*

iff

$B$  contains all infinite words  
that begin with a given prefix  $p$ .

- The *open sets* are the arbitrary unions of basic open sets.
- The *closed sets* are the complements of open sets.

# The Borel hierarchy

The *Borel hierarchy* is the most common classification of subsets of a given topological space. In our case, we first equip the Cantor space  $\mathcal{C}$  with the following topology:

- The *basic open sets* are the prefix  $\omega$ -languages i.e.

$B$  is a *basic open set*  
 iff  
 $B$  contains all infinite words  
 that begin with a given prefix  $p$ .

- The *open sets* are the arbitrary unions of basic open sets.
- The *closed sets* are the complements of open sets.





## Definition

The class of *Borel sets* of  $\mathcal{C}$  is the  $\sigma$ -algebra generated by the open sets, i.e. *Borel subsets* of  $\mathcal{C}$  are the  $\omega$ -languages that can be obtained from open sets by the operations of countable union and complementation.

## Definition

The class of *Borel sets* of  $\mathcal{C}$  is the  $\sigma$ -algebra generated by the open sets, i.e. *Borel subsets* of  $\mathcal{C}$  are the  $\omega$ -languages that can be obtained from open sets by the operations of countable union and complementation.

The *Borel hierarchy* classifies Borel sets according to how many times the operations of countable unions and complementation appear in their definitions.

## Definition

The *Borel finite levels* of the *Borel hierarchy* are defined by induction on  $n$  as follows:

- $\Sigma_1^0 = \{A \subseteq \mathcal{C} : A \text{ is open}\}$
- $\Sigma_{n+1}^0 = \{\bigcup_{n \in \mathbb{N}} A_n : A_n \in \Sigma_n^0\}$
- $\Pi_n^0 = \{A : A^c \in \Sigma_n^0\}$
- $\Delta_n^0 = \{A : A \in \Sigma_n^0 \cap \Pi_n^0\}$

The *Borel hierarchy* classifies Borel sets according to how many times the operations of countable unions and complementation appear in their definitions.

## Definition

The *Borel finite levels* of the *Borel hierarchy* are defined by induction on  $n$  as follows:

- $\Sigma_1^0 = \{A \subseteq \mathcal{C} : A \text{ is open}\}$
- $\Sigma_{n+1}^0 = \{\bigcup_{n \in \mathbb{N}} A_n : A_n \in \Sigma_n^0\}$
- $\Pi_n^0 = \{A : A^c \in \Sigma_n^0\}$
- $\Delta_n^0 = \{A : A \in \Sigma_n^0 \cap \Pi_n^0\}$

The *Borel hierarchy* classifies Borel sets according to how many times the operations of countable unions and complementation appear in their definitions.

## Definition

The *Borel finite levels* of the *Borel hierarchy* are defined by induction on  $n$  as follows:

- $\Sigma_1^0 = \{A \subseteq \mathcal{C} : A \text{ is open}\}$
- $\Sigma_{n+1}^0 = \{\bigcup_{n \in \mathbb{N}} A_n : A_n \in \Sigma_n^0\}$
- $\Pi_n^0 = \{A : A^c \in \Sigma_n^0\}$
- $\Delta_n^0 = \{A : A \in \Sigma_n^0 \cap \Pi_n^0\}$

The *Borel hierarchy* classifies Borel sets according to how many times the operations of countable unions and complementation appear in their definitions.

## Definition

The *Borel finite levels* of the *Borel hierarchy* are defined by induction on  $n$  as follows:

- $\Sigma_1^0 = \{A \subseteq \mathcal{C} : A \text{ is open}\}$
- $\Sigma_{n+1}^0 = \{\bigcup_{n \in \mathbb{N}} A_n : A_n \in \Sigma_n^0\}$
- $\Pi_n^0 = \{A : A^c \in \Sigma_n^0\}$
- $\Delta_n^0 = \{A : A \in \Sigma_n^0 \cap \Pi_n^0\}$

The *Borel hierarchy* classifies Borel sets according to how many times the operations of countable unions and complementation appear in their definitions.

## Definition

The *Borel finite levels* of the *Borel hierarchy* are defined by induction on  $n$  as follows:

- $\Sigma_1^0 = \{A \subseteq \mathcal{C} : A \text{ is open}\}$
- $\Sigma_{n+1}^0 = \{\bigcup_{n \in \mathbb{N}} A_n : A_n \in \Sigma_n^0\}$
- $\Pi_n^0 = \{A : A^c \in \Sigma_n^0\}$
- $\Delta_n^0 = \{A : A \in \Sigma_n^0 \cap \Pi_n^0\}$

The *Borel hierarchy* classifies Borel sets according to how many times the operations of countable unions and complementation appear in their definitions.


## Definition

The *Borel finite levels* of the *Borel hierarchy* are defined by induction on  $n$  as follows:


- $\Sigma_1^0 = \{A \subseteq \mathcal{C} : A \text{ is open}\}$
- $\Sigma_{n+1}^0 = \{\bigcup_{n \in \mathbb{N}} A_n : A_n \in \Sigma_n^0\}$
- $\Pi_n^0 = \{A : A^c \in \Sigma_n^0\}$
- $\Delta_n^0 = \{A : A \in \Sigma_n^0 \cap \Pi_n^0\}$




# The Borel Hierarchy




# The Borel Hierarchy




# The Borel Hierarchy



# The Borel Hierarchy




# The Borel Hierarchy



# The Borel Hierarchy

height  $\omega_1$


⋮



# The Borel Hierarchy

height  $\omega_1$


⋮



## The Borel Hierarchy

height  $\omega_1$ 

•  
•  
•  
•  
•





# The Wadge hierarchy

The Wadge hierarchy a drastic refinement of the Borel hierarchy.

## Definition

Let  $A$  and  $B$  subsets of the Cantor space  $\mathcal{C}$  (i.e. two  $\omega$ -languages). The *continuous reduction*  $\leq_w$  is defined by:

$$\begin{aligned} A \leq_w B & \quad \text{iff} \quad \text{there exists } f \text{ continuous s.t. } A = f^{-1}(B) \\ & \quad \text{iff} \quad \text{there exists } f \text{ continuous s.t. } x \in A \Leftrightarrow f(x) \in B \end{aligned}$$

Then as usual

$$A <_w B \quad \text{iff} \quad A \leq_w B \text{ and } B \not\leq_w A$$

$$A \equiv_w B \quad \text{iff} \quad A \leq_w B \text{ and } B \leq_w A$$



# The Wadge hierarchy

The Wadge hierarchy a drastic refinement of the Borel hierarchy.

## Definition

Let  $A$  and  $B$  subsets of the Cantor space  $\mathcal{C}$  (i.e. two  $\omega$ -languages). The *continuous reduction*  $\leq_w$  is defined by:

$$\begin{aligned} A \leq_w B \quad \text{iff} \quad & \text{there exists } f \text{ continuous s.t. } A = f^{-1}(B) \\ & \text{iff} \quad \text{there exists } f \text{ continuous s.t. } x \in A \Leftrightarrow f(x) \in B \end{aligned}$$

Then as usual

$$A <_w B \quad \text{iff} \quad A \leq_w B \text{ and } B \not\leq_w A$$

$$A \equiv_w B \quad \text{iff} \quad A \leq_w B \text{ and } B \leq_w A$$

# The Wadge hierarchy

The Wadge hierarchy a drastic refinement of the Borel hierarchy.

## Definition

Let  $A$  and  $B$  subsets of the Cantor space  $\mathcal{C}$  (i.e. two  $\omega$ -languages). The *continuous reduction*  $\leq_w$  is defined by:

$$\begin{aligned}
 A \leq_w B \quad \text{iff} \quad & \text{there exists } f \text{ continuous s.t. } A = f^{-1}(B) \\
 & \text{iff} \quad \text{there exists } f \text{ continuous s.t. } x \in A \Leftrightarrow f(x) \in B
 \end{aligned}$$

Then as usual

$$A <_w B \quad \text{iff} \quad A \leq_w B \text{ and } B \not\leq_w A$$

$$A \equiv_w B \quad \text{iff} \quad A \leq_w B \text{ and } B \leq_w A$$

$A \leq_W B$  means intuitively that  $A$  is “less complicated” than  $B$ .  
Indeed we have ...

$$A \leq_W B \quad \text{iff} \quad x \in A \Leftrightarrow f(x) \in B \quad \text{for some } f \text{ continuous}$$

In other terms, the belonging problem in  $A$  reduces via  $f$  to the belonging problem in  $B$ .

$A \leq_W B$  means intuitively that  $A$  is “less complicated” than  $B$ .  
Indeed we have ...

$$A \leq_W B \quad \text{iff} \quad x \in A \Leftrightarrow f(x) \in B \quad \text{for some } f \text{ continuous}$$

In other terms, the belonging problem in  $A$  reduces via  $f$  to the belonging problem in  $B$ .

$A \leq_W B$  means intuitively that  $A$  is “less complicated” than  $B$ .  
Indeed we have ...

$$A \leq_W B \quad \text{iff} \quad x \in A \Leftrightarrow f(x) \in B \quad \text{for some } f \text{ continuous}$$

**Assume that for any element  $x$ ,  
you know whether  $x \in B$  or not**

In other terms, the belonging problem in  $A$  reduces via  $f$  to the belonging problem in  $B$ .

$A \leq_W B$  means intuitively that  $A$  is “less complicated” than  $B$ .  
Indeed we have ...

$$A \leq_W B \quad \text{iff} \quad x \in A \Leftrightarrow f(x) \in B \text{ for some } f \text{ continuous}$$

Does a given  $a \in A$ ?

Assume that for any element  $x$ ,  
you know whether  $x \in B$  or not

In other terms, the belonging problem in  $A$  reduces via  $f$  to the belonging problem in  $B$ .



$A \leq_W B$  means intuitively that  $A$  is “less complicated” than  $B$ .  
Indeed we have ...

$$A \leq_W B \quad \text{iff} \quad x \in A \Leftrightarrow f(x) \in B \text{ for some } f \text{ continuous}$$

Does a given  $a \in A$ ?

Assume that for any element  $x$ ,  
you know whether  $x \in B$  or not

$$a \longmapsto f \longrightarrow f(a)$$

In other terms, the belonging problem in  $A$  reduces via  $f$  to the belonging problem in  $B$ .

$A \leq_W B$  means intuitively that  $A$  is “less complicated” than  $B$ .  
Indeed we have ...

$A \leq_W B$  iff  $x \in A \Leftrightarrow f(x) \in B$  for some  $f$  continuous

Does a given  $a \in A$ ?

Assume that for any element  $x$ ,  
you know whether  $x \in B$  or not

$a \longmapsto f \longrightarrow f(a)$

If  $f(a) \in B$ , then  $a \in A$

In other terms, the belonging problem in  $A$  reduces via  $f$  to the belonging problem in  $B$ .

$A \leq_W B$  means intuitively that  $A$  is “less complicated” than  $B$ .  
Indeed we have ...

$$A \leq_W B \quad \text{iff} \quad x \in A \Leftrightarrow f(x) \in B \text{ for some } f \text{ continuous}$$

Does a given  $a \in A$  ?

Assume that for any element  $x$ ,  
you know whether  $x \in B$  or not

$$a \longmapsto f \longrightarrow f(a)$$

If  $f(a) \in B$ , then  $a \in A$

If  $f(a) \notin B$ , then  $a \notin A$

In other terms, the belonging problem in  $A$  reduces via  $f$  to the belonging problem in  $B$ .

$A \leq_W B$  means intuitively that  $A$  is “less complicated” than  $B$ .  
Indeed we have ...

$$A \leq_W B \quad \text{iff} \quad x \in A \Leftrightarrow f(x) \in B \text{ for some } f \text{ continuous}$$

Does a given  $a \in A$  ?

Assume that for any element  $x$ ,  
you know whether  $x \in B$  or not

$$a \longmapsto f \longrightarrow f(a)$$

If  $f(a) \in B$ , then  $a \in A$

If  $f(a) \notin B$ , then  $a \notin A$


In other terms, the belonging problem in  $A$  reduces via  $f$  to the belonging problem in  $B$ .

## Definition

- The collection of all subsets of  $\mathcal{C}$  (i.e. all  $\omega$ -languages) ordered by the relation  $\leq_W$  is called *the Wadge hierarchy*.
- The collection of all Borel subsets of  $\mathcal{C}$  ordered by the relation  $\leq_W$  is called *the Borel Wadge hierarchy*.


## Theorem

*The Wadge hierarchy of Borel subsets of finite ranks has width 2 and height  $\underbrace{\omega_1^{\omega_1^{\omega_1^{\dots}}}}_{\omega \text{ times}}$  (huge!).*







## The Borel Hierarchy of finite ranks




## The Wadge Hierarchy




## The Borel Hierarchy of finite ranks



## The Wadge Hierarchy



## The Wagner Hierarchy





- The Wadge hierarchy is a very refined classification of  $\omega$ -languages.
- The Wadge hierarchy is a very refined classification of “anything that can be coded as  $\omega$ -languages”.
- The Wadge hierarchy of more complex languages (like tree languages) also exists.
- Descriptive set theory provides a general framework for classification problems.

- The Wadge hierarchy is a very refined classification of  $\omega$ -languages.
- The Wadge hierarchy is a very refined classification of “anything that can be coded as  $\omega$ -languages”.
- The Wadge hierarchy of more complex languages (like tree languages) also exists.
- Descriptive set theory provides a general framework for classification problems.

- The Wadge hierarchy is a very refined classification of  $\omega$ -languages.
- The Wadge hierarchy is a very refined classification of “anything that can be coded as  $\omega$ -languages”.
- The Wadge hierarchy of more complex languages (like tree languages) also exists.
- Descriptive set theory provides a general framework for classification problems.

- The Wadge hierarchy is a very refined classification of  $\omega$ -languages.
- The Wadge hierarchy is a very refined classification of “anything that can be coded as  $\omega$ -languages”.
- The Wadge hierarchy of more complex languages (like tree languages) also exists.
- Descriptive set theory provides a general framework for classification problems.