

ATTRACTOR-BASED COMPLEXITY AND LEARNING IN BOOLEAN NEURAL NETWORKS

APPLICATION TO A SIMPLIFIED MODEL OF THE BASAL GANGLIA-THALAMOCORTICAL NETWORK

Jérémie Cabessa
Joint work with Alessandro E.P. Villa

Department of Mathematical Economics
University Paris II
France

ICANN 17, September 13, 2017


INTRODUCTION

- ▶ We introduce an attractor-based complexity measure and learning procedure for Boolean recurrent neural networks.
- ▶ We illustrate these concepts in a simplified Boolean model of the basal ganglia-thalamocortical network.


INTRODUCTION

- ▶ We introduce an attractor-based complexity measure and learning procedure for Boolean recurrent neural networks.
- ▶ We illustrate these concepts in a simplified Boolean model of the basal ganglia-thalamocortical network.

RECURRENT NEURAL NETWORK



BOOLEAN RECURRENT NEURAL NETWORK




$$x_i(t+1) = \theta \left(\sum_{j=1}^N a_{ij} \cdot x_j(t) + \sum_{j=1}^M b_{ij} \cdot u_j(t) + c_i \right)$$

ATTRACTORS AND CYCLES


Boolean Neural Network

Automaton




ATTRACTORS AND CYCLES

Boolean Neural Network




Automaton




ATTRACTORS AND CYCLES

Boolean Neural Network



Automaton




Input stream




ATTRACTORS AND CYCLES

Boolean Neural Network



Automaton



Input stream




Sequence of states




ATTRACTORS AND CYCLES

Boolean Neural Network



Automaton




Input stream



Sequence of states




Raster plot




ATTRACTORS AND CYCLES

Boolean Neural Network

ATTRACTOR



Automaton




Input stream



Sequence of states




Raster plot



ATTRACTORS AND CYCLES


Boolean Neural Network

ATTRACTOR



Automaton

CYCLE




Input stream



Sequence of states



Raster plot



ATTRACTOR-BASED COMPLEXITY OF RNNs

- ▶ We assume that some aspects of the computational capabilities of recurrent neural networks are related to their attractor dynamics.
- ▶ We introduce attractor-based complexity measure inspired from automata theory.
- ▶ We assume that the attractors are classified into two categories: meaningful or spurious.
- ▶ The attractor-based complexity refers to the maximal number of meaningful and spurious attractors that are included one into the other.

ATTRACTOR-BASED COMPLEXITY OF RNNs

- ▶ We assume that some aspects of the computational capabilities of recurrent neural networks are related to their attractor dynamics.
- ▶ We introduce attractor-based complexity measure inspired from automata theory.
- ▶ We assume that the attractors are classified into two categories: meaningful or spurious.
- ▶ The attractor-based complexity refers to the maximal number of meaningful and spurious attractors that are included one into the other.

ATTRACTOR-BASED COMPLEXITY OF RNNs

- ▶ We assume that some aspects of the computational capabilities of recurrent neural networks are related to their attractor dynamics.
- ▶ We introduce attractor-based complexity measure inspired from automata theory.
- ▶ We assume that the attractors are classified into two categories: meaningful or spurious.
- ▶ The attractor-based complexity refers to the maximal number of meaningful and spurious attractors that are included one into the other.

ATTRACTOR-BASED COMPLEXITY OF RNNs


- ▶ We assume that some aspects of the computational capabilities of recurrent neural networks are related to their attractor dynamics.
- ▶ We introduce attractor-based complexity measure inspired from automata theory.
- ▶ We assume that the attractors are classified into two categories: meaningful or spurious.
- ▶ The attractor-based complexity refers to the maximal number of meaningful and spurious attractors that are included one into the other.

ATTRACTOR-BASED COMPLEXITY OF BRNNs


Example:

- Assume that \mathcal{N} contains only one meaningful attractor; all others being spurious.
- Then, the attractor-based complexity of \mathcal{N} is 3. Maximal “growing” and “alternating” sequence of 3 attractors.

Boolean Neural Network



Automaton




ATTRACTOR-BASED COMPLEXITY OF BRNNs


Example:

- Assume that \mathcal{N} contains only one meaningful attractor; all others being spurious.
- Then, the attractor-based complexity of \mathcal{N} is 3. Maximal “growing” and “alternating” sequence of 3 attractors.

Boolean Neural Network



Automaton




ATTRACTOR-BASED COMPLEXITY OF BRNNs


Example:

- Assume that \mathcal{N} contains only one meaningful attractor; all others being spurious.
- Then, the attractor-based complexity of \mathcal{N} is 3. Maximal “growing” and “alternating” sequence of 3 attractors.

Boolean Neural Network




Automaton




ATTRACTOR-BASED COMPLEXITY OF BRNNs

Example:

- ▶ Assume that \mathcal{N} contains only one meaningful attractor; all others being spurious.
- ▶ Then, the attractor-based complexity of \mathcal{N} is 3. Maximal “growing” and “alternating” sequence of 3 attractors.




BOOLEAN MODEL OF THE BASAL GANGLIA-THALAMOCORTICAL NETWORK



| | |
|-----------------|--|
| IN | input node |
| SC | superior colliculus |
| GPi/SNr | output nuclei of the basal ganglia formed by the GABAergic projection neurons of the intermediate part of the pallidum and of the substantia nigra pars reticulata |
| Thalamus | thalamus |
| GPe | external part of the pallidum |
| NRT | thalamic reticular nucleus |
| Str-D1 | striatopallidal component of the striatum |
| Str-D2 | striatonigral component of the striatum |
| STN | subthalamic nucleus |
| Cerebral Cortex | cerebral cortex |

BOOLEAN MODEL OF THE BASAL GANGLIA-THALAMOCORTICAL NETWORK





| | |
|-----------------|--|
| IN | input node |
| SC | superior colliculus |
| GPi/SNr | output nuclei of the basal ganglia formed by the GABAergic projection neurons of the intermediate part of the pallidum and of the substantia nigra pars reticulata |
| Thalamus | thalamus |
| GPe | external part of the pallidum |
| NRT | thalamic reticular nucleus |
| Str-D1 | striatopallidal component of the striatum |
| Str-D2 | striatonigral component of the striatum |
| STN | subthalamic nucleus |
| Cerebral Cortex | cerebral cortex |

BOOLEAN MODEL OF THE BASAL GANGLIA-THALAMOCORTICAL NETWORK


| Source | Target (Node #) | | | | | | | | | |
|---------------|------------------------|-----|-----|------|------|------|------|------|------|---|
| Node # (Name) | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| 0 (IN) | . | 1 | 1 | . | . | . | . | . | . | . |
| 1 (SC) | int₁ | . | 1 | . | . | . | . | . | . | . |
| 2 (Thalamus) | . | . | . | 1 | . | 1 | 1 | 1 | 1 | 1 |
| 3 (RTN) | . | . | -1 | . | . | . | . | . | . | . |
| 4 (GPi/SNr) | . | -1 | -1 | -1 | . | . | . | . | . | . |
| 5 (STN) | . | . | . | . | 2 | . | 2 | . | . | 2 |
| 6 (GPe) | . | . | . | -1/2 | -1/2 | -1/2 | . | -1/2 | -1/2 | . |
| 7 (Str-D2) | . | . | . | . | . | . | -1 | . | . | . |
| 8 (Str-D1) | . | . | . | . | -1/2 | . | -1/2 | . | . | . |
| 9 (CCortex) | int₂ | 1/2 | 1/2 | 1/2 | . | 1/2 | . | 1/2 | 1/2 | . |

TABLE: Adjacency matrix


CORRESPONDING AUTOMATON




ATTRACTORS AND CYCLES




ATTRACTORS AND CYCLES




ATTRACTOR-BASED COMPLEXITY AND LEARNING IN BRNNs








ATTRACTORS AND CYCLES




ATTRACTORS AND CYCLES









ATTRACTORS AND CYCLES







ATTRACTORS AND CYCLES




ATTRACTORS AND CYCLES




ATTRACTORS AND CYCLES




ATTRACTORS AND CYCLES




ATTRACTORS AND CYCLES



ATTRACTORS AND CYCLES



ATTRACTORS AND CYCLES



ATTRACTOR-BASED COMPLEXITY

Meaningfulness criterion

- ▶ A constitutive cycle – i.e., a basic attractor – is *spurious* if it is characterised either by active SC and quiet Thalamus at the same time step, or by a quiet GPi/SNr during the majority of the duration of the cycle.
- ▶ A constitutive cycle is *meaningful* otherwise.
- ▶ A non-constitutive cycle – i.e., a composed attractor – is considered *meaningful* if it contains a majority of meaningful constitutive cycles.
- ▶ A non-constitutive cycle is *spurious* otherwise.

ATTRACTOR-BASED COMPLEXITY

Meaningfulness criterion

- ▶ A constitutive cycle – i.e., a basic attractor – is *spurious* if it is characterised either by active SC and quiet Thalamus at the same time step, or by a quiet GPi/SNr during the majority of the duration of the cycle.
- ▶ A constitutive cycle is *meaningful* otherwise.
- ▶ A non-constitutive cycle – i.e., a composed attractor – is considered *meaningful* if it contains a majority of meaningful constitutive cycles.
- ▶ A non-constitutive cycle is *spurious* otherwise.

ATTRACTOR-BASED COMPLEXITY

Meaningfulness criterion

- ▶ A constitutive cycle – i.e., a basic attractor – is *spurious* if it is characterised either by active SC and quiet Thalamus at the same time step, or by a quiet GPi/SNr during the majority of the duration of the cycle.
- ▶ A constitutive cycle is *meaningful* otherwise.
- ▶ A non-constitutive cycle – i.e., a composed attractor – is considered *meaningful* if it contains a majority of meaningful constitutive cycles.
- ▶ A non-constitutive cycle is *spurious* otherwise.

ATTRACTOR-BASED COMPLEXITY


Meaningfulness criterion

- ▶ A constitutive cycle – i.e., a basic attractor – is *spurious* if it is characterised either by active SC and quiet Thalamus at the same time step, or by a quiet GPi/SNr during the majority of the duration of the cycle.
- ▶ A constitutive cycle is *meaningful* otherwise.
- ▶ A non-constitutive cycle – i.e., a composed attractor – is considered *meaningful* if it contains a majority of meaningful constitutive cycles.
- ▶ A non-constitutive cycle is *spurious* otherwise.

ATTRACTOR-BASED COMPLEXITY



- In the corresponding automaton, we have a maximal ‘growing’ and “alternating” sequence of 7 cycles (attractors).

Attractor-based
complexity





degree 7


SYNAPTIC PLASTICITY'S INFLUENCE ON THE NETWORK'S ATTRACTORS



SYNAPTIC PLASTICITY'S INFLUENCE ON THE NETWORK'S ATTRACTORS




NUMBER OF ATTRACTORS (FCT OF INT. WEIGHTS): GLOBAL THRESHOLD (OR WEIGHTS) MODIFICATIONS




Lowering the global threshold, i.e., potentiating the global synaptic level, increases the maximal numbers of attractors and improves the robustness of the “no interactivity” configuration.

NUMBER OF ATTRACTORS (FCT OF INT. WEIGHTS): GLOBAL THRESHOLD (OR WEIGHTS) MODIFICATIONS




Lowering the global threshold, i.e., potentiating the global synaptic level, increases the maximal numbers of attractors and improves the robustness of the “no interactivity” configuration.

NUMBER OF ATTRACTORS (FCT OF INT. WEIGHTS): GLOBAL THRESHOLD (OR WEIGHTS) MODIFICATIONS




Lowering the global threshold, i.e., potentiating the global synaptic level, increases the maximal numbers of attractors and improves the robustness of the “no interactivity” configuration.

NUMBER OF ATTRACTORS (FCT OF INT. WEIGHTS): GLOBAL THRESHOLD (OR WEIGHTS) MODIFICATIONS




Lowering the global threshold, i.e., potentiating the global synaptic level, increases the maximal numbers of attractors and improves the robustness of the “no interactivity” configuration.

NUMBER OF ATTRACTORS (FCT OF INT. WEIGHTS): GLOBAL THRESHOLD (OR WEIGHTS) MODIFICATIONS




Lowering the global threshold, i.e., potentiating the global synaptic level, increases the maximal numbers of attractors and improves the robustness of the “no interactivity” configuration.

NUMBER OF ATTRACTORS (FCT OF INT. WEIGHTS): GLOBAL THRESHOLD (OR WEIGHTS) MODIFICATIONS



Lowering the global threshold, i.e., potentiating the global synaptic level, increases the maximal numbers of attractors and improves the robustness of the “no interactivity” configuration.

ATTRACTOR COMPLEXITY (FCT OF INT. WEIGHTS): LOCAL WEIGHTS MODIFICATIONS




Even single weight variations of ± 0.1 can significantly affect the complexity pattern.

INPUT DISCRIMINATION


- ▶ An input stream s is *discriminated* by a sequence of attractors $\mathcal{C} = (C_0, \dots, C_n)$ if the network, when receiving input s stream s , visits the successive attractors C_0, \dots, C_n of \mathcal{C} .
- ▶ The *discriminability degree* of s , $d^*(s)$, is the length of a maximal sequence of attractors \mathcal{C} that discriminates s .

input stream s
01001100111000111001...



INPUT DISCRIMINATION

- ▶ An input stream s is *discriminated* by a sequence of attractors $\mathcal{C} = (C_0, \dots, C_n)$ if the network, when receiving input s stream s , visits the successive attractors C_0, \dots, C_n of \mathcal{C} .
- ▶ The *discriminability degree* of s , $d^*(s)$, is the length of a maximal sequence of attractors \mathcal{C} that discriminates s .



INPUT DISCRIMINATION

- ▶ We introduce an *attractor-based learning procedure* which updates the (interactive) network's weights in order to achieve a targeted discriminability degree of some input stream s .


Algorithm 1 Attractor-based learning procedure

Require: input stream s ; initial weights w_1, w_2 ; target discriminability degree N^*

- 1: compute $d^*(s)$
 - 2: **while** $d^*(s) < N^*$ **do**
 - 3: $w_k \leftarrow f(w_k)$, for $k = 1, \dots, N$
 - 4: compute $d^*(s)$ for the network with updated weights w_k , for $k = 1, \dots, N$
 - 5: **end while**
 - 6: **return** w_k , for $k = 1, \dots, N$
-

$$f(w_k) = w_k + step \cdot \frac{-sum(m_s)}{len(m_s)} \cdot \left(1 + \frac{len(m_s) - d^*(s)}{len(m_s)}\right) + \epsilon$$

INPUT DISCRIMINATION



CONCLUSIONS

- ▶ Global and local modifications of the *synaptic weights* significantly affect the attractor complexity of the networks.
- ▶ The values of the *interactive connections* also play a significant role in the maintenance and robustness of an optimal level of attractor-based complexity.
- ▶ We have an *attractor-based learning procedure* which modifies the interactive weight in order to reach a targeted discriminability degree of a certain input stream.
- ▶ These considerations support the rationale that *synaptic plasticity* might be crucially involved in the computational capabilities of neural networks.

CONCLUSIONS

- ▶ Global and local modifications of the *synaptic weights* significantly affect the attractor complexity of the networks.
- ▶ The values of the *interactive connections* also play a significant role in the maintenance and robustness of an optimal level of attractor-based complexity.
- ▶ We have an *attractor-based learning procedure* which modifies the interactive weight in order to reach a targeted discriminability degree of a certain input stream.
- ▶ These considerations support the rationale that *synaptic plasticity* might be crucially involved in the computational capabilities of neural networks.

CONCLUSIONS

- ▶ Global and local modifications of the *synaptic weights* significantly affect the attractor complexity of the networks.
- ▶ The values of the *interactive connections* also play a significant role in the maintenance and robustness of an optimal level of attractor-based complexity.
- ▶ We have an *attractor-based learning procedure* which modifies the interactive weight in order to reach a targeted discriminability degree of a certain input stream.
- ▶ These considerations support the rationale that *synaptic plasticity* might be crucially involved in the computational capabilities of neural networks.

CONCLUSIONS

- ▶ Global and local modifications of the *synaptic weights* significantly affect the attractor complexity of the networks.
- ▶ The values of the *interactive connections* also play a significant role in the maintenance and robustness of an optimal level of attractor-based complexity.
- ▶ We have an *attractor-based learning procedure* which modifies the interactive weight in order to reach a targeted discriminability degree of a certain input stream.
- ▶ These considerations support the rationale that *synaptic plasticity* might be crucially involved in the computational capabilities of neural networks.