

# The Algebraic Counterpart of the Wagner Hierarchy

Jérémie Cabessa & Jacques Duparc

University of Lausanne

June 20, 2008

# Outline

## 1 Introduction

## 2 The Wagner hierarchy

## 3 $\omega$ -Semigroups

## 4 The FSG-hierarchy

## 5 Conclusion

# Outline

## 1 Introduction

## 2 The Wagner hierarchy

## 3 $\omega$ -Semigroups

## 4 The FSG-hierarchy

## 5 Conclusion

# Outline

## 1 Introduction

## 2 The Wagner hierarchy

## 3 $\omega$ -Semigroups

## 4 The FSG-hierarchy


## 5 Conclusion

# Outline

- 1 Introduction
- 2 The Wagner hierarchy
- 3  $\omega$ -Semigroups
- 4 The FSG-hierarchy
- 5 Conclusion

# Outline

- 1 Introduction
- 2 The Wagner hierarchy
- 3  $\omega$ -Semigroups
- 4 The FSG-hierarchy
- 5 Conclusion



# The Wagner Hierarchy

(most refined classification of  $\omega$ -rational languages)

Given two  $\omega$ -rational languages  $K$  and  $L$ , we set

$K \leq_w L$  iff  $K = f^{-1}(L)$  for some continuous function  $f$   
 iff  $w \in K \Leftrightarrow f(w) \in L$  for some continuous function  $f$   
 iff Player II has a w.s. in the Wadge game  $W(K, L)$

Then as usual,  $K <_w L$  iff  $K \leq_w L \not\leq_w K$  and  $K \equiv_w L$  iff  $K \leq_w L \leq_w K$ .

## Definition (Wagner hierarchy)

The collection of all  $\omega$ -rational languages ordered by the relation  $\leq_w$  is called *the Wagner hierarchy*.



# The Wagner Hierarchy

(most refined classification of  $\omega$ -rational languages)

Given two  $\omega$ -rational languages  $K$  and  $L$ , we set

$$\begin{aligned}
 K \leq_w L \quad \text{iff} \quad & K = f^{-1}(L) \text{ for some continuous function } f \\
 & \text{iff} \quad w \in K \Leftrightarrow f(w) \in L \text{ for some continuous function } f \\
 & \text{iff} \quad \text{Player II has a w.s. in the Wadge game } W(K, L)
 \end{aligned}$$

Then as usual,  $K <_w L$  iff  $K \leq_w L$  and  $K \not\equiv_w L$  and  $K \equiv_w L$  iff  $K \leq_w L \leq_w K$ .

## Definition (Wagner hierarchy)

The collection of all  $\omega$ -rational languages ordered by the relation  $\leq_w$  is called *the Wagner hierarchy*.

# The Wagner Hierarchy

(most refined classification of  $\omega$ -rational languages)

Given two  $\omega$ -rational languages  $K$  and  $L$ , we set

$$\begin{aligned}
 K \leq_w L \quad &\text{iff} \quad K = f^{-1}(L) \text{ for some continuous function } f \\
 &\text{iff} \quad w \in K \Leftrightarrow f(w) \in L \text{ for some continuous function } f \\
 &\text{iff} \quad \text{Player II has a w.s. in the Wadge game } W(K, L)
 \end{aligned}$$

Then as usual,  $K <_w L$  iff  $K \leq_w L \not\leq_w K$  and  $K \equiv_w L$  iff  $K \leq_w L \leq_w K$ .

## Definition (Wagner hierarchy)

The collection of all  $\omega$ -rational languages ordered by the relation  $\leq_w$  is called *the Wagner hierarchy*.

# The Wagner Hierarchy

(most refined classification of  $\omega$ -rational languages)

Given two  $\omega$ -rational languages  $K$  and  $L$ , we set

- $$K \leq_w L \quad \text{iff} \quad K = f^{-1}(L) \text{ for some continuous function } f$$
- $$\text{iff} \quad w \in K \Leftrightarrow f(w) \in L \text{ for some continuous function } f$$
- $$\text{iff} \quad \text{Player II has a w.s. in the Wadge game } W(K, L)$$

Then as usual,  $K <_w L$  iff  $K \leq_w L$  and  $K \not\equiv_w L$  and  $K \equiv_w L$  iff  $K \leq_w L \leq_w K$ .

## Definition (Wagner hierarchy)

The collection of all  $\omega$ -rational languages ordered by the relation  $\leq_w$  is called *the Wagner hierarchy*.

# The Wagner Hierarchy

(most refined classification of  $\omega$ -rational languages)

Given two  $\omega$ -rational languages  $K$  and  $L$ , we set

$$\begin{aligned}
 K \leq_w L \quad \text{iff} \quad & K = f^{-1}(L) \text{ for some continuous function } f \\
 \text{iff} \quad & w \in K \Leftrightarrow f(w) \in L \text{ for some continuous function } f \\
 \text{iff} \quad & \text{Player II has a w.s. in the Wadge game } W(K, L)
 \end{aligned}$$

Then as usual,  $K <_w L$  iff  $K \leq_w L \not\leq_w K$  and  $K \equiv_w L$  iff  $K \leq_w L \leq_w K$ .

## Definition (Wagner hierarchy)

The collection of all  $\omega$ -rational languages ordered by the relation  $\leq_w$  is called *the Wagner hierarchy*.

## The Wagner Hierarchy

(most refined classification of  $\omega$ -rational languages)

Given two  $\omega$ -rational languages  $K$  and  $L$ , we set

$$\begin{aligned}
 K \leq_w L \quad \text{iff} \quad & K = f^{-1}(L) \text{ for some continuous function } f \\
 & \text{iff} \quad w \in K \Leftrightarrow f(w) \in L \text{ for some continuous function } f \\
 & \text{iff} \quad \text{Player II has a w.s. in the Wadge game } W(K, L)
 \end{aligned}$$

Then as usual,  $K <_w L$  iff  $K \leq_w L \not\leq_w K$  and  $K \equiv_w L$  iff  $K \leq_w L \leq_w K$ .

### Definition (Wagner hierarchy)


The collection of all  $\omega$ -rational languages ordered by the relation  $\leq_w$  is called *the Wagner hierarchy*.

## Theorem (Wagner 79)

*The Wagner hierarchy has height  $\omega^\omega$  and it is decidable.*


## Theorem (Wagner 79)

*The Wagner hierarchy has height  $\omega^\omega$  and it is decidable.*





# Theorem (Wagner 79)

*The Wagner hierarchy has height  $\omega^\omega$  and it is decidable.*









## Definition ( $\omega$ -semigroup)

An  $\omega$ -semigroup  $S$  is a pair  $(S_+, S_\omega)$ , where  $S_+$  is a semigroup,  $S_\omega$  is a set, and equipped with

- an associative mixed product :  $S_+ \times S_\omega \longrightarrow S_\omega$
- a surjective infinite product  $\pi_S : S_+^\omega \longrightarrow S_\omega$  satisfying

$$\pi_S(s_0 s_1 \cdots s_{k_1-1}, s_{k_1} \cdots s_{k_2-1}, \dots) = \pi_S(s_0, s_1, s_2, \dots),$$

$$s \pi_S(s_0, s_1, s_2, \dots) = \pi_S(s, s_0, s_1, s_2, \dots).$$

A *pointed  $\omega$ -semigroup* is a pair  $(S, X)$ , where

- $S = (S_+, S_\omega)$  is an  $\omega$ -semigroup,
- $X \subseteq S_\omega$ .

## Definition ( $\omega$ -semigroup)

An  $\omega$ -semigroup  $S$  is a pair  $(S_+, S_\omega)$ , where  $S_+$  is a semigroup,  $S_\omega$  is a set, and equipped with

- an associative mixed product :  $S_+ \times S_\omega \longrightarrow S_\omega$
- a surjective infinite product  $\pi_S : S_+^\omega \longrightarrow S_\omega$  satisfying

$$\pi_S(s_0 s_1 \cdots s_{k_1-1}, s_{k_1} \cdots s_{k_2-1}, \dots) = \pi_S(s_0, s_1, s_2, \dots),$$

$$s \pi_S(s_0, s_1, s_2, \dots) = \pi_S(s, s_0, s_1, s_2, \dots).$$

A *pointed  $\omega$ -semigroup* is a pair  $(S, X)$ , where

- $S = (S_+, S_\omega)$  is an  $\omega$ -semigroup,
- $X \subseteq S_\omega$ .

## Definition ( $\omega$ -semigroup)

An  $\omega$ -semigroup  $S$  is a pair  $(S_+, S_\omega)$ , where  $S_+$  is a semigroup,  $S_\omega$  is a set, and equipped with

- an associative mixed product :  $S_+ \times S_\omega \longrightarrow S_\omega$
- a surjective infinite product  $\pi_S : S_+^\omega \longrightarrow S_\omega$  satisfying

$$\pi_S(s_0 s_1 \cdots s_{k_1-1}, s_{k_1} \cdots s_{k_2-1}, \dots) = \pi_S(s_0, s_1, s_2, \dots),$$

$$s \pi_S(s_0, s_1, s_2, \dots) = \pi_S(s, s_0, s_1, s_2, \dots).$$

A *pointed  $\omega$ -semigroup* is a pair  $(S, X)$ , where

- $S = (S_+, S_\omega)$  is an  $\omega$ -semigroup,
- $X \subseteq S_\omega$ .

## Definition ( $\omega$ -semigroup)

An  $\omega$ -semigroup  $S$  is a pair  $(S_+, S_\omega)$ , where  $S_+$  is a semigroup,  $S_\omega$  is a set, and equipped with

- an associative mixed product :  $S_+ \times S_\omega \longrightarrow S_\omega$
- a surjective infinite product  $\pi_S : S_+^\omega \longrightarrow S_\omega$  satisfying

$$\pi_S(s_0 s_1 \cdots s_{k_1-1}, s_{k_1} \cdots s_{k_2-1}, \dots) = \pi_S(s_0, s_1, s_2, \dots),$$

$$s \pi_S(s_0, s_1, s_2, \dots) = \pi_S(s, s_0, s_1, s_2, \dots).$$

A *pointed  $\omega$ -semigroup* is a pair  $(S, X)$ , where

- $S = (S_+, S_\omega)$  is an  $\omega$ -semigroup,
- $X \subseteq S_\omega$ .

## Finite pointed $\omega$ -semigroups are the algebraic counterparts of Büchi automata.

### Theorem

*An  $\omega$ -language is recognizable by a finite pointed  $\omega$ -semigroup iff it is recognizable by a finite Büchi (or Muller) automaton (iff it is  $\omega$ -rational).*


**Finite pointed  $\omega$ -semigroups are the algebraic counterparts of Büchi automata.**

## Theorem

*An  $\omega$ -language is recognizable by a finite pointed  $\omega$ -semigroup iff it is recognizable by a finite Büchi (or Muller) automaton (iff it is  $\omega$ -rational).*



Among all finite pointed  $\omega$ -semigroups recognizing a given  $\omega$ -rational language  $L$ , there exists a minimal one, **the syntactic  $\omega$ -semigroup** of  $L$ , denoted by  $Synt(L)$ .



We aim to classify finite pointed  $\omega$ -semigroups. We adopt a hierarchical game approach.

We transpose Wadge games on  $\omega$ -semigroups...

We aim to classify finite pointed  $\omega$ -semigroups. We adopt a hierarchical game approach.

**We transpose Wadge games on  $\omega$ -semigroups...**

We aim to classify finite pointed  $\omega$ -semigroups. We adopt a hierarchical game approach.

**We transpose Wadge games on  $\omega$ -semigroups...**

Let  $S = (S_+, S_\omega)$  and  $T = (T_+, T_\omega)$  be two finite  $\omega$ -semigroups, and let also  $X \subseteq S_\omega$  and  $Y \subseteq T_\omega$ .

The infinite two-player game  $\text{SG}(X, Y)$  is defined as follows:

- Player I plays elements from  $S_+$ ,
- Player II plays elements from  $T_+$ ,
- players I and II play alternately, Player I begins,
- Player II may skip her turn, Player I is not allowed,

Let  $S = (S_+, S_\omega)$  and  $T = (T_+, T_\omega)$  be two finite  $\omega$ -semigroups, and let also  $X \subseteq S_\omega$  and  $Y \subseteq T_\omega$ .

The infinite two-player game  $\text{SG}(X, Y)$  is defined as follows:

- Player I plays elements from  $S_+$ ,
- Player II plays elements from  $T_+$ ,
- players I and II play alternately, Player I begins,
- Player II may skip her turn, Player I is not allowed,

Let  $S = (S_+, S_\omega)$  and  $T = (T_+, T_\omega)$  be two finite  $\omega$ -semigroups, and let also  $X \subseteq S_\omega$  and  $Y \subseteq T_\omega$ .

The infinite two-player game  $\text{SG}(X, Y)$  is defined as follows:

- Player I plays elements from  $S_+$ ,
- Player II plays elements from  $T_+$ ,
- players I and II play alternately, Player I begins,
- Player II may skip her turn, Player I is not allowed,

Let  $S = (S_+, S_\omega)$  and  $T = (T_+, T_\omega)$  be two finite  $\omega$ -semigroups, and let also  $X \subseteq S_\omega$  and  $Y \subseteq T_\omega$ .

The infinite two-player game  $\text{SG}(X, Y)$  is defined as follows:

- Player I plays elements from  $S_+$ ,
- Player II plays elements from  $T_+$ ,
- players I and II play alternately, Player I begins,
- Player II may skip her turn, Player I is not allowed,



Let  $S = (S_+, S_\omega)$  and  $T = (T_+, T_\omega)$  be two finite  $\omega$ -semigroups, and let also  $X \subseteq S_\omega$  and  $Y \subseteq T_\omega$ .

The infinite two-player game  $\text{SG}(X, Y)$  is defined as follows:

- Player I plays elements from  $S_+$ ,
- Player II plays elements from  $T_+$ ,
- players I and II play alternately, Player I begins,
- Player II may skip her turn, Player I is not allowed,



■ Player II wins the game  $\text{SG}(X, Y)$  iff

$$\pi_S(s_0, s_1, \dots) \in X \Leftrightarrow \pi_T(t_0, t_1, \dots) \in Y.$$

## Definition (SG-reduction)

We write  $(S, X) \leq_{\text{SG}} (T, Y)$  iff Player II has a winning strategy in  $\text{SG}(X, Y)$ . And as usual  $(S, X) \equiv_{\text{SG}} (T, Y)$  iff  $(S, X) \leq_{\text{SG}} (T, Y) \leq_{\text{SG}} (S, X)$ .



■ Player II wins the game  $\text{SG}(X, Y)$  iff

$$\pi_S(s_0, s_1, \dots) \in X \Leftrightarrow \pi_T(t_0, t_1, \dots) \in Y.$$

## Definition (SG-reduction)

We write  $(S, X) \leq_{\text{SG}} (T, Y)$  iff Player II has a winning strategy in  $\text{SG}(X, Y)$ . And as usual  $(S, X) \equiv_{\text{SG}} (T, Y)$  iff  $(S, X) \leq_{\text{SG}} (T, Y) \leq_{\text{SG}} (S, X)$ .



■ Player II wins the game  $\text{SG}(X, Y)$  iff

$$\pi_S(s_0, s_1, \dots) \in X \Leftrightarrow \pi_T(t_0, t_1, \dots) \in Y.$$

## Definition (SG-reduction)

We write  $(S, X) \leq_{\text{SG}} (T, Y)$  iff Player II has a winning strategy in  $\text{SG}(X, Y)$ . And as usual  $(S, X) \equiv_{\text{SG}} (T, Y)$  iff  $(S, X) \leq_{\text{SG}} (T, Y) \leq_{\text{SG}} (S, X)$ .



■ Player II wins the game  $\text{SG}(X, Y)$  iff

$$\pi_S(s_0, s_1, \dots) \in X \Leftrightarrow \pi_T(t_0, t_1, \dots) \in Y.$$

## Definition ( $\text{SG}$ -reduction)

We write  $(S, X) \leq_{\text{SG}} (T, Y)$  iff Player II has a winning strategy in  $\text{SG}(X, Y)$ . And as usual  $(S, X) \equiv_{\text{SG}} (T, Y)$  iff  $(S, X) \leq_{\text{SG}} (T, Y) \leq_{\text{SG}} (S, X)$ .

## Definition (FSG-hierarchy)

The collection of finite pointed  $\omega$ -semigroups ordered by the  $\leq_{SG}$ -relation is called *the FSG-hierarchy*.

## Theorem


*The FSG-hierarchy and the Wagner hierarchy are isomorphic.*



# Corollary

*The FSG-hierarchy has height  $\omega^\omega$ , and it is decidable.*

decidability procedure









*The FSG-hierarchy has height  $\omega^\omega$ , and it is decidable.*

## decidability procedure



### The Wagner hierarchy




### The FSG-hierarchy

# Corollary

*The FSG-hierarchy has height  $\omega^\omega$ , and it is decidable.*

decidability procedure



*The FSG-hierarchy has height  $\omega^\omega$ , and it is decidable.*

height  $\omega^0$

...

$L(\mathcal{A}) = L(S, X)$

The Wagner hierarchy

$Synt[(S, X)] \equiv_{sg} (S, X)$

???

height  $\omega^0$


...

The FSG-hierarchy

# Corollary

*The FSG-hierarchy has height  $\omega^\omega$ , and it is decidable.*


decidability procedure



# Corollary

*The FSG-hierarchy has height  $\omega^\omega$ , and it is decidable.*


decidability procedure



## Corollary

*The FSG-hierarchy has height  $\omega^\omega$ , and it is decidable.*

decidability procedure



## Corollary

*Let  $L$  be an  $\omega$ -rational language. Then  $d_W(L) = \alpha$  iff  $d_{sg}(\text{Synt}(L)) = \alpha$ .*

## Conclusions

- The FSG-hierarchy is the algebraic counterpart of the Wagner hierarchy.
- Decidability procedure of the FSG-hierarchy.
- One can compute the Wagner degree of an  $\omega$ -rational language directly on its syntactic image.
- Build a finite pointed  $\omega$ -semigroup of any given Wagner degree.



## Conclusions

- The FSG-hierarchy is the algebraic counterpart of the Wagner hierarchy.
- Decidability procedure of the FSG-hierarchy.
- One can compute the Wagner degree of an  $\omega$ -rational language directly on its syntactic image.
- Build a finite pointed  $\omega$ -semigroup of any given Wagner degree.

## Conclusions

- The FSG-hierarchy is the algebraic counterpart of the Wagner hierarchy.
- Decidability procedure of the FSG-hierarchy.
- **One can compute the Wagner degree of an  $\omega$ -rational language directly on its syntactic image.**
- Build a finite pointed  $\omega$ -semigroup of any given Wagner degree.

## Conclusions

- The FSG-hierarchy is the algebraic counterpart of the Wagner hierarchy.
- Decidability procedure of the FSG-hierarchy.
- **One can compute the Wagner degree of an  $\omega$ -rational language directly on its syntactic image.**
- Build a finite pointed  $\omega$ -semigroup of any given Wagner degree.